



Highlights:

- Improve cost-effectiveness with higher performance per watt
- Simplify management and serviceability with flexible design
- Manage risk with resilient architectures and virtualized environments



IBM System x3650 M3

Performance-optimized server for mission-critical applications

Packed with innovation

The IBM System x3650 M3 provides outstanding performance for your mission-critical applications. Its energy-efficient design supports more cores, memory and disk capacity in a scalable 2U package that's easy to service and manage. With more computing power per watt and the latest Intel Xeon processors, you can reduce costs while maintaining speed and availability.

Simplify management and serviceability

The x3650 M3 offers a flexible, scalable design and simple upgrade path to 16 HDDs or SSDs, and 288 GB of memory. Comprehensive systems management tools such as advanced diagnostics, a cable management arm and the ability to control resources from a single point make it easy to deploy, integrate, service and manage.

Reduce risk and maintain availability

With new 6 Gbps RAID adapters integrated and double the I/O performance, the x3650 M3 provides a resilient architecture ideal for mission-critical applications as well as virtualization environments. Advanced memory support and greater disk capacity let you take advantage of higher processing speeds without sacrificing uptime.

Select configurations of the x3650 M3 are part of the IBM Express Advantage® Portfolio designed to meet the needs of mid-sized businesses. Easy to manage, Express® models and configurations vary by country.





© Copyright IBM Corporation 2011

IBM Systems and Technology Group
Route 100
Somers, New York 10589

June 2011
All Rights Reserved

IBM, the IBM logo, ibm.com and System x are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both. If these and other IBM trademarked terms are marked on their first occurrence in this information with a trademark symbol (® or ™), these symbols indicate U.S. registered or common law trademarks owned by IBM at the time this information was published. Such trademarks may also be registered or common law trademarks in other countries. A current list of IBM trademarks is available on the web at “Copyright and trademark information” at ibm.com/legal/copytrade.shtml

Intel and Intel Xeon are registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Linux is a registered trademark of Linus Torvalds in the United States, other countries or both.

Microsoft is a registered trademark of Microsoft Corporation in the United States, other countries or both.

Other product, company or service names may be trademarks or service marks of others.



Please Recycle

IBM System x3650 M3 at a glance

Form factor/height	Rack/2U
Processor (max)	Up to two 3.46 GHz six-core (3.60 GHz four-core) Intel Xeon 5600 series processors with QuickPath Interconnect technology
Number of processors (std/max)	1/2
Cache (max)	Up to 12 MB L3
Memory (max)	288 GB DDR-3 RDIMMs via 18 DIMM slots or 48 GB DDR-3 UDIMMs via 12 DIMM slots
Expansion slots	4
Disk bays (total/hot swap)	Up to sixteen 2.5 in. hot-swap SAS/SATA HDDs or SSDs
Maximum internal storage	Up to 16 TB (hot-swap SAS/SATA)
Network interface	Integrated 2 ports, plus 2 ports optional Gigabit Ethernet
Power supply (std/max)	1/2; 460 W, 675 W, 675 W high efficiency or 675 W DC (model dependent)
Hot-swap components	Power supplies, fan modules, disks
RAID support	6 Gbps RAID-0, -1, -10 or 6 Gbps RAID-0, -1, -10, -5, -50 with 256 MB or 512 MB cache and additional option battery backup (model dependent)
NEBS 1/ETSI compliance	Equivalent compliance for both AC and DC power supply (model dependent)
Energy-efficiency compliance	Compliant with 80-PLUS® and ENERGY STAR® energy-efficiency standards (model dependent)
Systems management	IBM IMM with Virtual Media Key for optional remote presence enablement, Predictive Failure Analysis, Diagnostic LEDs, light path diagnostics panel, Automatic Server Restart, IBM Systems Director and IBM Systems Director Active Energy Manager™
Operating systems supported	Microsoft Windows Server 2008 R2 and 2008, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESX and ESXi, Oracle Solaris 10 (model dependent)
Limited warranty	3-year customer replaceable unit and onsite limited warranty

For more information

U.S. ibm.com/systems/x/

Canada ibm.com/systems/ca/en/servers/x/index.html